

Product description

The PX-03 release hook meets the high SOLAS standards for release hooks, as described in the MSC.81(70) and applicable LSA code, and is dimensioned to suspend davit launched rescue boats with a davit load not exceeding 1.500 kg.

Pictures



Dimensions

Art.no: PX03

Width	Length	Height	Weight
260 mm	135 mm	60 mm	4,5 kg

HS code: 7326.9090

Certificates & Standards

Approved by:
RINA

Standards:
• Complies with SOLAS MSC.81(70)

Instructions:
• Use non-rotating wire rope
• Use a painter line where possible
• Use a shackle \varnothing 19 mm up to \varnothing 27 mm

Applications & Use

Installation of the hook is easy, disassemble the top shaft by removing the hexagonal securing screw, and unscrewing the nut which holds the shaft in position. Place the spliced eye or corresponding wire rope fall over the distance bush. Place the distance bush between the two side plates and place the shaft. Then make sure the shaft is fastened tightly and the hexagonal securing screw is put back in place.

Specifications

Maximum Safe Working Load: 1500 kg
Material: Seawater resistant stainless steel

Operation:
The PX-03 is a manual release hook. All hook handling can be done by one person. The hook is designed to be opened manually, just push the release handle in the upward position and the hook will open.