Datasheet LIFE RAFT/RESCUE BOAT HOOK PXOI



Product description

The T-ISS Life Raft/Rescue Boat Hook is a combined automatic release hook which can handle rescue boats and life rafts up to a safe working load of 35kN.

The advantage of using the T-ISS PX01 is two-fold;

- It will increase safety, as the crew only need to familiarize themselves with one hook, instead of two.
 Also there is no second hook, dangerously swinging around when lowering.
 - In distress situations the crew will instantly know which hook to use, as there is only one hook.
- Secondly it is economical, why buy two hooks if one is sufficient?

Pictures



Dimensions

Art.no: PX01

Dimensions: 285x260x70 mm

With Length Height Weight 260 mm 285 mm 70 mm 7 kg

HS code: 7326.9090

Certificates & Standards

Approved by:

- EC Directive 96/98EC on Marine Equipment (MED) Relevant standard:
- LSA Code for Hooks for Life raft Launching, as amended MSC.81(70)
- Fully compliant with updated SOLAS requirements as per Resolutions MSC.320(89) and MSC.321(80)
- Rina No. MED 000816ws/002

Applications & Use

This hook can be used for rescue boats with a davit load less than 3500 kg and/or a davit launched life raft up to 40 pax. The hook can be operated as an automatic release hook, releasing when the craft enters the water, or as a manual release hook, whereby the load needs to be off the hook before releasing.

Specifications

Maximum Safe Working Load: 3500 kg Material: Stainless steel 316/Duplex

