





## Totally Enclosed Lifeboat JYN-50





Product code: 1310104100

Self-righting, unsinkable Totally Enclosed Lifeboat, with a weight of 2435 kg and maximum capacity of 22 persons provides safety and protection for personnel and passengers in extreme weather conditions. Constructed with fire-retardant glass-fibre reinforced polyester.

It is launched by a cantilevered platform davit or single pivot davit. Designed to withstand powerful winds and high waves. The lifeboat is self-righting and unsinkable, even if damaged or fully flooded.

Prime embarkation to the lifeboat is through the side hatches, while additional access is via a large embarkation door.

The lifeboat is equipped with mechanical steering, located at the aft.



Comlies with IMO/SOLAS requirements, LSA Code, MED 2014/90.

phone: +38 (048) 733-33-39

www.markogroup.com

email: welcome@markogroup.com











Product code: 1310104100



- Constructed with fire-retardant glass-fibre reinforced polyester (GRP);
- Launched by a cantilevered platform davit or single pivot davit;
- · Positive stability up to 180 degrees;
- · Can be delivered as Tanker/Offshore or Dry Cargo version;

## Boat specifications:

- Length overall 5,06 m;
- · Beam 2,20 m;
- · Height 3,10 m;
- · Capacity, SOLAS maximum 22 persons;
- · Weight, fully equipped 2435 kg;
- · Davit load, with 22 pers. = 4250 kg;
- · External Color Orange (RAL 2004);
- Internal Color Light Gray (RAL 7032);
- Operation temperature from -15°C to +40°C;
- Hull/deck material fire retardant glass reinforced polyester;
- · Buoyancy material polyurethane foam;
- Windows toughened glass with glass-reinforced plastic (GRP) frame;
- Bollards/towing aft bollard, painter hook in bow;
- Steering mechanical;
- Hatches: 1 aft door / 1 side door each side / 1 top hatch / 1 front top hatch;

phone: +38 (048) 733-33-39 email: welcome@markogroup.com